



Quick Product Selector

Product Information

- ▶ [Features](#)
- ▶ [Specifications](#)
- ▶ [Agency Approvals](#)
- ▶ [Photo Gallery](#)
- ▶ [Documents](#)
- ▶ [Part Numbers](#)

Menu Selections

- ▶ [Multi-Status and Stackable](#)
- ▶ [Hazardous Location Visual Signals](#)
- ▶ [Flashing Beacons](#)
- ▶ [Rotating Beacons](#)
- ▶ [Steady-On Beacons](#)
- ▶ [Strobes](#)

Product Part Numbers

102 Series

Trioptical Stackable Status Indicator

DeviceNet™, PLC Compatible

Part Number	Description	DIV 1	DIV 2	Outdoor	NEMA 4X	Marine	PLC
023001	Replacement Cap for 102 Series						
102DMBS-G1	Direct Mount Base 24 VDC, 1.75 Amp Max.		✓	✓			✓
102DMBS-N5	Direct Mount Base 120 VAC 50/60 Hz, 0.60 Amp Max.		✓	✓			✓
102LM-A	Lens Module Amber		✓	✓			
102LM-B	Lens Module Blue		✓	✓			
102LM-C	Lens Module Clear		✓	✓			
102LM-G	Lens Module Green		✓	✓			
102LM-R	Lens Module Red		✓	✓			
102LS-FIN-G1	Flashing Incandescent Light Source 24 VDC, 0.32 A		✓	✓			
102LS-FINH-G1	Flashing Halogen Light Source 24 VDC, 0.32 A		✓	✓			✓
102LS-FINH-N5	Flashing Halogen Light Source 120 VAC 50/60 Hz, 0.11A \$64.70		✓	✓			✓
			✓	✓			

102LS-SLEDG-N5	Steady-On LED Light Source Green 120 VAC 50/60 Hz, 0.022 A			✓	✓		✓
102LS-SLEDR-G1	Steady-On LED Light Source Red 24 VDC, 0.062 A			✓	✓		✓
102LS-SLEDR-N5	Steady-On LED Light Source Red 120 VAC 50/60 Hz, 0.022 A			✓	✓		✓
102LS-SLEDW-G1	Steady-On LED Light Source White 24 VDC, 0.062 A			✓	✓		✓
102LS-SLEDW-N5	Steady-On LED Light Source White 120 VAC 50/60 Hz, 0.022 A			✓	✓		✓
102LS-ST-G1	Strobe Light Source 24 VDC, 0.30 A			✓	✓		✓
102LS-ST-N5	Strobe Light Source 120 VAC 50/60 Hz, 0.12 A						
102MP-10	10" Pipe						
102MP-15	15" Pipe						
102MP-4	4" Pipe						
102PMBS-G1	Pipe Mount Base 24 VDC, 1.75 Amp Max.			✓	✓		✓
102PMBS-N5	Pipe Mount Base 120 VAC 50/60 Hz, 0.60 Amp Max.			✓	✓		✓
102PMF	Pipe Mount Flange						
102SIGMT-DN-G1	Device Net Tone Module 24 VDC 24 VDC, 0.05 A			✓	✓		✓
102SIGMT-G1	Multi-Tone, Tone Module 24 VDC, 0.05 A			✓	✓		✓
102SIGMT-N5	Multi-Tone, Tone Module 120 VAC 50/60 Hz, 0.05 A			✓	✓		✓
102SIGST-G1	Single Tone, Tone Module 24 VDC, 0.05 A			✓	✓		✓
102SIGST-N5	Single Tone, Tone Module 120 VAC 50/60 Hz, 0.05 A			✓	✓		✓
102SIN-RBA-G1	Pre-assembled 3 High Stack (Red/Blue/Amber) Red/Blue/Amber 24 VDC, 0.96 A			✓	✓		✓

102SIN-RBA-N5	Pre-assembled 3 High Stack (Red/Blue/Amber) Red/Blue/Amber 120 VAC 50/60 Hz, 0.24 A				
102SIN-RGA-G1	Pre-assembled 3 High Stack (Red/Green/Amber) Red/Green/Amber 24 VDC, 0.96 A		✓	✓	✓
102SIN-RGA-N5	Pre-assembled 3 High Stack (Red/Green/Amber) Red/Green/Amber 120 VAC 50/60 Hz, 0.24 A		✓	✓	✓
102TBS-DN-G1	DeviceNet Base 24 VDC 24 VDC, 1.75 Amps Max.		✓	✓	✓
102TBS-DN-N5	DeviceNet Base 120 VAC 120 VAC 50/60 Hz, 0.6 Amps Max.		✓	✓	✓
102TBS-G1	Pipe Mount Base with Tone Module Capacity 24 VDC, 1.75 Amp Max.		✓	✓	✓
102TBS-N5	Pipe Mount Base with Tone Module Capacity 120 VAC 50/60 Hz, 0.60 Amp Max.		✓	✓	✓